

# SAE100 R4 ULTIMATE FLEXIBILITY GMVRB04

## Corrugated Cover




TUBE : HYDRAULIC OIL RESISTANT SPECIAL SYNTHETIC RUBBER.  
 REINFORCEMENT : TWO HIGH TENSILE SYNTHETIC TEXTILE AND STEEL WIRE HELIX.  
 COVER : OIL, HEAT, ABRASION, OZONE AND WEATHER RESISTANT SYNTHETIC RUBBER(CORRUGATED).  
 APPLICATION : FOR WATER SUCTION/DISCHARGE AND HYDRAULIC RETURN/SUCTION OR PETROLEUM TRANSFER.  
 TEMPERATURE RANGE : -40°C~+100°C / -40°F~+212°F  
 NOTE : VACCUM PRESSURE: -0.84BAR

TYPE	SIZE		ID (mm)		OD (mm)	WP		BP		BR/r	W	L
	Dash Size	inch	min	max	max	bar	psi	bar	psi	mm	g/m	max/m
GMVRB04-19	-12	3/4"	18.2	19.8	34.9	21	305	84	1218	19	650	40/60
GMVRB04-25	-16	1"	24.6	26.2	41.3	17	247	68	986	25	800	40/60
GMVRB04-32	-20	1-1/4"	30.6	33.0	50.8	16	232	64	928	32	990	40/60
GMVRB04-38	-24	1-1/2"	36.9	39.3	57.2	16	232	64	928	38	1120	40/60
GMVRB04-51	-32	2"	49.2	52.4	69.9	16	232	48	696	51	1500	40/60
GMVRB04-60	-38	2-3/8"	55.5	60.5	73.5	16	232	48	696	60	2160	40/60
GMVRB04-64	-40	2-1/2"	61.9	65.1	82.6	16	232	48	696	64	2250	40/60
GMVRB04-76	-48	3"	74.6	77.8	95.3	10	145	30	435	76	2650	40/60
GMVRB04-89	-56	3-1/2"	87.3	90.5	107.9	10	145	30	435	90	3160	40/60
GMVRB04-102	-64	4"	100	103.2	120.7	10	145	30	435	102	3650	40/60
GMVRB04-127	-80	5"	126	128	145	10	145	30	435	130	5530	40/60
GMVRB04-152	-96	6"	151	153	171	10	145	30	435	150	6660	40/60



MARKING / TRANSFER TAPE

 **100 R4 ULTIMATE FLEXIBILITY(\*\*\*) (DN\*\*mm) W.P.\*\*BAR/\*\*PSI \*Q/\*\*\*\*(YEAR)**

NORMS		COLOUR	 BLACK
-------	--	--------	--