


4 Steel Wire Spiral



TUBE : MINERAL, VEGETABLE AND HYDRAULIC OIL RESISTANT SPECIAL SYNTHETIC RUBBER.
 REINFORCEMENT : 4 HIGH TENSILE STEEL SPIRAL.
 COVER : HYDRAULIC OIL, ABRASION AND WEATHER RESISTANT SPECIAL SYNTHETIC RUBBER.
 APPLICATION : FOR HYDRAULIC SYSTEMS WITH HIGH PEAK PRESSURES AND ARDUOUS OPERATING CONDITIONS.
 TEMPERATURE RANGE : -40°C~+100°C / -40°F~+212°F

TYPE	SIZE		ID (mm)		ROD (mm)		OD (mm)		WP		BP		BR/r	W	L
	Dash Size	inch	min	max	min	max	min	max	bar	psi	bar	psi	mm	g/m	max/m
ES61-064SP	-4	1/4	6.2	7.0	14.1	15.3	17.1	18.7	450	6525	1800	26100	150	640	20/40
ES61-104SP	-6	3/8	9.4	10.1	16.9	18.1	20.6	22.2	445	6450	1780	25810	180	750	20/40
ES61-134SP	-8	1/2	12.6	13.5	19.4	21.0	23.8	25.4	415	6020	1660	24070	230	890	20/40
ES61-164SP	-10	5/8	15.8	16.7	23.0	24.6	27.4	29.0	350	5075	1400	20300	250	1100	20/40
ES61-194SP	-12	3/4	18.8	19.8	27.4	29.0	31.4	33.0	350	5075	1400	20300	300	1500	20/40
ES61-254SP	-16	1	25.4	26.4	34.5	36.1	38.5	40.9	280	4060	1120	16240	340	2000	20/40
ES61-324SP	-20	1-1/4	31.8	33.0	45.0	47.0	49.2	52.4	210	3045	840	12180	460	3000	20/40
ES61-384SP	-24	1-1/2	38.0	39.3	51.4	53.4	55.6	58.8	185	2680	740	10730	560	3400	20/40
ES61-514SP	-32	2	50.6	52.0	64.3	66.3	68.2	71.4	165	2390	660	9570	660	4350	20/40

OPTIONS



MSHA

MARKING/TRANSFER TAPE,EMBOSSSED OR INK JET

NORMS	EN856	COLOUR	 BLACK
-------	-------	--------	--