


PRESSURE WASH HOSE

WM32

2 Steel Wire Braid



TUBE : MINERAL, VEGETABLE AND HYDRAULIC OIL RESISTANT SPECIAL SYNTHETIC RUBBER.
 REINFORCEMENT : 2 HIGH TENSILE STEEL WIRE BRAID.
 COVER : OIL, ABRASION AND WEATHER RESISTANT SPECIAL SYNTHETIC RUBBER.
 APPLICATION : FOR MEDIUM-HIGH PRESSURE CLEANING APPLICATIONS WITH HOT WATER TEMPERATURES UP TO 135°C
 TEMPERATURE RANGE : -40°C~+135°C / -40°F~+275°F

TYPE	SIZE		ID (mm)		ROD (mm)		OD (mm)	WP		BP		BR/r	W	L
	Dash Size	inch	min	max	min	max	max	bar	psi	bar	psi	mm	g/m	max/m
WM-06	-04	1/4"	6.4	7.0	12.1	13.3	15.7	400	5800	1600	23200	100	445	50/100
WM-08	-05	5/16"	7.9	8.5	13.7	14.9	17.3	350	5075	1400	20300	115	505	50/100
WM-10	-06	3/8"	9.5	10.1	16.1	17.3	19.7	330	4785	1320	19140	130	625	50/100
WM-13	-08	1/2"	12.7	13.5	19.0	20.6	23.0	275	3988	1100	15950	180	735	50/100
WM-16	-10	5/8"	15.8	16.7	22.2	23.8	26.2	250	3625	1000	14500	200	865	50/100
WM-19	-12	3/4"	18.8	19.8	26.2	27.8	30.1	215	3118	860	12470	240	1060	50/100
WM-25	-16	1"	25.4	26.4	34.1	35.7	38.9	165	2393	660	9570	300	1430	50/100





OPTIONS



SMOOTH COVER

MSHA

MARKING/TRANSFER TAPE,EMBOSSSED OR INK JET

NORMS	EN 853	COLOUR	   
			BLACK BLUE RED GRAY