

STEAM HOSE

HB04-01

1 Steel Wire Braid



- TUBE : MINERAL, VEGETABLE AND HOT WATER RESISTANT SYNTHETIC RUBBER.
- REINFORCEMENT : 1 HIGH TENSILE STEEL WIRE BRAID.
- COVER : PIN PRICKED, ABRASION AND WEATHER RESISTANT SPECIAL SYNTHETIC RUBBER.
- APPLICATION : FOR CONVEYING SATURATED STEAM AND HEATED CONDENSATE WATER WITH TEMPERATURE UP TO 210°C.
- TEMPERATURE RANGE : -40°C~+210°C / -40°F~+410°F


TYPE	SIZE		ID (mm)		ROD (mm)		OD (mm)		WP		BP		BR/r	W	L
	Dash Size	inch	min	max	min	max	min	max	bar	psi	bar	psi	mm	g/m	max/m
HB04-1001	-6	3/8"	9.5	10.5	15.4	16.2	18.7	19.7	6	87	60	870	150	315	50/100
HB04-1301	-8	1/2"	12.5	13.5	19.0	19.8	21.9	22.9	6	87	60	870	200	435	50/100
HB04-1601	-10	5/8"	15.5	16.5	22.1	22.9	25.0	26.0	6	87	60	870	240	495	50/100
HB04-1901	-12	3/4"	18.5	19.5	24.9	25.7	27.7	29.3	6	87	60	870	290	600	50/100
HB04-2201	-14	7/8"	21.5	22.5	28.1	28.9	31.0	32.0	6	87	60	870	330	630	50/100
HB04-2501	-16	1"	24.6	26.2	31.6	32.4	34.2	35.8	6	87	60	870	380	750	50/100
HB04-3201	-20	1-1/4"	31.8	32.8	38.7	39.7	41.5	43.5	6	87	60	870	480	955	20/40
HB04-3801	-24	1-1/2"	37.8	38.8	46.0	47.0	49.0	51.0	6	87	60	870	570	1095	20/40

OPTIONS



MSHA

MARKING/TRANSFER TAPE,EMBOSSSED OR INK JET

NORMS		COLOUR	 BLACK
-------	--	--------	--